



Feigete Intellient Technology Co.,Limited

ADD: 2 Floor,Building No.51,Bantian No.3 Industrial Area,Longgang District,Shenzhen
TEL:86-755-82338710 FAX:86-755-28751866 website: www.smartfeigete.com

Android Commercial Tablet with docking charge Model No: SF1099T



Processor	CPU	RK3576S Quad core cortex A72+Quad core cortex A53,Maximum frequency 2.2GHz
	GPU	ARM G52 MC3
	NPU	3 TOPS
	RAM	4GB
	nternal memory	64GB
	Operation system	Android 14
Display	Panel Size	10.95" In cell
	Resolution	1200*1920
	Color Gamut	56% Clight
	Viewing angle	R/L 80/80, U/D 80/80
	Contrast ratio	1500: 1
	Luminance	280 nits
	Backlight life	30000h
	Aspect Ratio	16:10
Touch	Touch type	Capacitive touch screen
	Number of points	10-Point
Network	WiFi	IEEE 802.11a/b/g/n/ac/ax(Wi-Fi 6)
	Bluetooth	Bluetooth 5.4
	2G&3G&4G	/
Camera	Front camera	500W Fixed focus
	Rear camera	1300W Auto focus (AF)
Battery	Type	Lithium Battery
	Capacity	3.8V/8000mAh
	Battery life	5-7 hours
Interface	Type C	Support: Charging and OTG
	Headphone jack	Support 3.5mm 4 knots with MIC
	SD	/
	TF	Support up to 512GB
	Docking	Support charging
Multimedia	Button	3 physical buttons (power button/volume +/- buttons)
	Decoder	H.264,H.265,VP9,AV1,AVS2,JPEG
	Encoder	H.264,H.265,JPEG
Other	Product Colors	Black
	G-Sensor	Support
	Speaker	8Ω/1W *4
	Microphone	Single wheat
	FM	Support
	NFC	Standard configuration,NXP PN7160, ISO/IEC 18092(NFCIP-1),ISO/IEC 21481(NFCIP-2),ISO/IEC 14443A,ISO/IEC 14443B,ISO/IEC 15693,Mifare Classic,Mifare Ultralight,MIFARE DESFire EV1/ EV2 ,Sony FelIca
	Light sensor	/
	Gyro	/
	Hall function	/
	GNSS	/
	Vibration	/
	Wireless charging	/
	Certificates	FCC/CE/ROHS; GMS; Buyer Need to pay for certificates.
Working Surrounding	Working Temperature	0℃—40℃
	Storage Temperature	-20℃—60℃
	Working Humidity	20~80%RH
	Storage Humidity	10~95%RH
Accessories	Adapter	● Standard configuration: 5V/2A ● Optional: 12V/5A Note: ● The 5V/2A adapter can be used for both the machine and the charging dock. When used with the charging dock, it only supports charging a single machine. ● When multiple charging docks are connected for use, one 12V/5A adapter is required. A single charging dock does not come with a 12V/5A adapter.
	USB cable	Standard configuration*1
	Charging base	Standard configuration*1
	Leather cover + nylon strap	Standard configuration*1
	Suspenders	Standard configuration*1
	User manual	Standard configuration*1

Product Measurement, mm

Unit (Without packaging)			Giftbox (With Packaging)			Carton 2pcs/CTN		
L	W	H	L	W	H	L	W	H
257.3	169.46	9.85						
N.W(kg)			N.W(kg)			N.W(kg)		
						G.W		

Drawing



